

REV. Status

REVISION -
02/29/96 TSREVISION A
ADDED RoHS
12/01/05 MPREVISION B
NOTE 7 WAS $\pm 20\%$
04/19/06 MPREVISION C
ADDED TEMP
RATING
4/29/15 MP

AUDIO COUPLING MINIATURE ENCAPSULATED TRANSFORMER DESIGNED TO OPERATE 30mW MAX IN SECONDARY AND REFLECT A PRIMARY SOURCE IMPEDANCE OF APPROXIMATELY 25K Ω CT WITH 1K Ω CT LOAD ON SECONDARY.

A. Electrical Specifications (@ 20 ° C)

1. Pri Source Impedance; 25K Ω CT
2. Sec Load Impedance; 1K Ω CT
3. Pri DC Current; 0.5 mA MAX
4. Operating Level; 30 mW MAX @ 300 Hz
5. Frequency Response (relative to 1 KHz);
 ± 2.0 dB, @ 300 Hz to 100 KHz
6. Longitudinal Balance; 60 dB MIN @ 1 KHz
7. DC Resistance;
(1-3) 1600 Ω $\pm 20\%$
(4-6) 95 Ω -20%, +30%
8. Turns Ratio; (1-3) : (4-6) = 5.00 : 1 $\pm 2\%$
9. Dielectric Strength;
60Hz 500Vrms 0.5 minute @ Pri - Sec





MODEL NUMBER

MET-05


B. Marking; MET-05, TAMURA, Primary and Secondary Impedance,
PM11-M, MICROTRAN, TF5S21ZZ, date code and country of origin

- C. Operating Temperature: -20 to +85°C
Storage Temperature: -55 to +105°C

D. Schematic Diagram

Date code, and
country of origin

E. Mechanical Specifications



TOLERANCES (mm)

≤ 4	± 0.2
$4 \leq 20$	± 0.3
$20 \leq 50$	± 0.4

PREPARED BY:

C. POPPE

ENGINEER:

MATHI P.

SAFETY ENGINEER

DRAWING CONTROL NO.

P-A1-11577

REV

C

MODEL DESCRIPTION

AUDIO COUPLING
MINIATURE ENCAPSULATED XFMR

MODEL SPECIFICATION

MET-05

CONTENTS OF THIS DRAWING ARE
SUBJECT TO CHANGE WITHOUT
PRIOR NOTICETAMURA CORPORATION OF AMERICA
1040 SOUTH ANDREASEN DRIVE, #100 ESCONDIDO, CA. 92029
(951) 699-1270 FAX 7607400536

DIM: mm[In] SCL: 2/1 SH: 1 OF 1

APPROVED:

M. PITCHAI

PROPRIETARY NOTICE: THIS DRAWING PRINT OR DOCUMENT AND SUBJECT MATTER DISCLOSED HEREIN ARE PROPRIETARY ITEMS TO WHICH TAMURA RETAINS THE EXCLUSIVE RIGHT OF DISSEMINATION, REPRODUCTION, MANUFACTURE AND SALE. THIS DRAWING, PRINT OR DOCUMENT IS SUBMITTED IN CONFIDENCE FOR CONSIDERATION BY THE RECIPIENT ALONE UNLESS PERMISSION FOR FURTHER DISCLOSURE IS EXPRESSLY GRANTED IN WRITING.